

Bake & Peel Conductive Foil Tape



Nolato PPT "Bake & Peel" tape provides an effective alternative to selective plating or Alocrom on painted enclosures.

The (conductive) adhesive foil tape is fixed in place prior to painting; once painting and baking are completed the peel off mask can be removed to expose a conductive foil surface to which an EMC gasket can be fixed.

Aluminium tapes are held as stock parts, copper and conductive fabric types are available to order.

PART NUMBER	WIDTH	DESCRIPTION	MATERIAL THICKNESS	PEEL ADHESION	ELECTRICAL RESISTANCE
TF-1013 TF-1025	13mm 25mm	Aluminium 'Bake & Peel' Tape	0.05mm	1060	<0.03 Ω
TF-2013 TF-2025	13mm 25mm	Copper 'Bake & Peel' Tape	0.05mm	1080	<0.03 Ω
TF-3013 TF-3025	13mm 25mm	Conductive Fabric 'Bake & Peel' Tape	0.093mm	1220	<0.03 Ω

Standard roll length is 25m

Adhesive thickness on all variants is 0.04mm

Temperature specification (baking) 1 hour at 200°C



Nolato PPT
Unit 12, Maldon Trade Park, The Causeway
Maldon, Essex, CM9 4LJ, UK
Tel: +44 (0) 1376 550525 Fax: +44 (0) 01376 552389
Email: sale.ppt@nolato.com Web: www.p-p-t.co.uk

